

## Din 766 Windlass Stainless Steel Chain - G50 316L

Titan™ AISI 316L Stainless Steel Chain is designed to offer superior corrosion resistance, appearance and strength. Made in Germany, each link is precisely calibrated to meet current DIN 766 windlass specifications, and manufactured with an extra treatment to provide exceptionally smooth and clean surfaces. Please check manufacturer's specification prior to use.

PID	Description	Wire Diameter	Internal Length	Standard Length	Net Weight	Breaking Strength	Working Load Limit
10321050	6mm-35m DIN766 G50 SS316L Chain	6mm	18.5mm	35m	24kg	30kn	7.5kn
10321051	6mm-50m DIN766 G50 SS316L Chain	6mm	18.5mm	50m	35kg	30kn	7.5kn
10319630	6mm-100m DIN766 G50 SS316L Chain	6mm	18.5mm	100m	69kg	30kn	7.5kn
10321060	8mm-35m DIN766 G50 SS316L Chain	8mm	24mm	35m	44kg	50kn	12.5kn
10321061	8mm-50m DIN766 G50 SS316L Chain	8mm	24mm	50m	62kg	50kn	12.5kn
10319631	8mm-100m DIN766 G50 SS316L Chain	8mm	24mm	100m	124kg	50kn	<b>12.</b> 5kn
10321070	10mm-35m P28 DIN766 G50 SS316L Chain	10mm	28mm	35m	72kg	80kn	20kn
10321071	10mm-50m P28 DIN766 G50 SS316L Chain	10mm	28mm	50m	103kg	80kn	20kn
10319632	10mm-100m P28 DIN766 G50 SS316L Chain	10mm	28mm	100m	206kg	80kn	20kn

Finish: Polished Stainless Steel

Packaging: Pails & Half Drums

Made in Germany

T: 1-604-940-2010 sales@canmet.com titanmarineproducts.com



